

RESTROOM FIXTURES

MURDOCK-SUPER SECUR RESTROOM

MODEL # 1013


FIXTURE


LAVATORY WITH DECK-MOUNTED VALVE

















Note: Fixture may show some available options



ROUGH-IN-DIMENSIONS

TECHNICAL DATA:

Fixture is designed to be installed on a finished wall and serviced from the front side. Fixture is fabricated from 16 gage, type 304 stainless steel and is seamless welded construction. Exterior has a satin finish.

Rectangular lavatory bowl is 14" x 12" x 6" deep. Lavatory deck has an integral self-draining soap dish.

Lavatory valves conform to lead free requirements of NSF61, Section 9, 1997 and CHSC 116875.

Regularly furnished items include wall mounting bracket, grid strainer with tailpiece and 1-1/4" x 1-1/2" tubular P-trap. Mounting screws are supplied by installer. Insulation may be required (supplied by installer) for drain lines on layatories with hot and cold valves.

MODEL NUMBER:

□ 1013-9 Lavatory less Valve (3-hole)
 □ 1013-H1-9 Lavatory less Valve (1-hole)
 □ 1013-CSSA Lavatory with Hot and Cold Valve
 □ 1013-SO2 Lavatory with Cold Only Sensor Valve

Lavatory with Cold Only Valve

PRODUCT OPTIONS:

☐ 1013-STS

☐ -EG Enviro-Glaze (for color selection see flier)

See Options on Sheet LAV-OPT

		▲ WARNING: Cancer and Reproductive Har	rm - www.P65Warnings.ca.gov
ECTION SUMMARY APPROVAL FOR AANUFACTURING	Model Number & Options_	_Quantity	All dimensions are nominal and subject to change without notice. Murdock-Super Secur assumes
NAL CTUF	Company		no responsibility for use of void or superseded data. Murdock Mfg. ¹
CTION	ContactTitle	,	Member of Morris Group International™. Please visit
SELE & A MA	Signature (Approval for Manufacturing)	Data	www.murdockmfg.com for most current specifications.

MURDOCK-SUPER SECUR • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP