



DRINKING FOUNTAIN

A132 Series

MODEL A132400S-BF4

BARRIER FREE, BI-LEVEL, WALL MOUNTED DRINKING FOUNTAIN WITH SEMI-RECESSED SENSOR OPERATED BOTTLE FILLER AND 32" TRIM PANEL

STANDARD FEATURES

- Both Child or Adult ADA Compliant (when properly installed)
- 18 gage, 304 stainless steel bowl
- Polished Lead-Free Stainless Steel, anti-rotation non-squirt Bubbler or Flexible Low Flow Bubbler
- 100 mesh inlet strainer
- Mounting frame
- 32" wide trim panel
- 1 G.P.M. Fill Rate (Bottle Filler)
- Laminar Flow Water Supply (Bottle Filler)
- 115v Plug-in Transformer (Bottle Filler)

SUGGESTED SPECIFICATIONS

Model A132400S-BF4 is a wall mounted, bi-level drinking fountain and bottle filler combination made from 18 gage, 304 stainless steel with a brushed finish. Fountain shall be activated by self-closing, frontal push pads, by using less than 5 pounds of force, which activates internally mounted valves with adjustable stream regulators controlling the water flow. Bottle filler activates using an infrared sensor. Bubblers shall be polished stainless steel with non-squirt features and operate on a water pressure range of 20-105 psig. Unit shall have uniquely designed, two-piece contoured bowls with P-traps integral to the unit. Fountain is certified to ANSI A117.1, NSF/ANSI 61, Section 9, Public Law 111-380 (NO-LEAD), and CHSC 116875. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.



Model A132400S-BF4-BCD Shown
** U.S. DESIGN PATENT D545,607

MODEL:

(Must Specify)

FLEXIBLE BUBBLER (LOW FLOW)

- A132200F-BF4 Bronze Finish
- A132300F-BF4 Gold Finish (High Polish)
- A132400F-BF4 Satin stainless Finish

LEAD-FREE STAINLESS STEEL BUBBLER

- A132200S-BF4 Bronze Finish
- A132300S-BF4 Gold Finish (High Polish)
- A132400S-BF4 Satin stainless Finish (Shown)

OPTIONS

(additional costs may be incurred)

- AP3 Access Panel for a Dual Fountain
- BCD Bottle Counter Display (Bottle Filler)
- HP High Polished Stainless Steel
- RBL Reverse Bi-Level (Bottle Filler Opposite)
- SK4 Skirt Kit, Stainless Steel, for upper unit
- WF1 1500-gallon capacity, NSF 42+53, 1 micron Lead Reduction Filter
- A9100080-A 8 GPH Remote Water Chiller (Recommended to be with 10 Feet of Fixture)

Complies with the following standards:



Member of U.S. Green Building Council



Recyclable Product



Water Conserving Product

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA
Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP INTERNATIONAL

