

GR Series

MODEL GRE24

BARRIER FREE, WALL MOUNTED, ANGLED,
BI-LEVEL DRINKING FOUNTAIN

STANDARD FEATURES

- Both Child or Adult ADA Compliant (when properly installed)
- Optionally Available with "Hands Free" Controls
- 18 Gauge, 304 Stainless Steel Bowls
- 12 Gauge, Heavy Duty Stainless Steel Arm, Corrosion and Scratch Resistant Finish
- Heavy Duty Stainless Steel, Vandal Resistant Bottom Access Panels
- 1/4" Thick Stainless Steel Mounting Plate
- Pushbutton With Cartridge Valve Assembly
- Polished Stainless Steel, Anti-Rotation, Non-Squirt Bubbler
- Resistant to Sunlight, Heat, Moisture and Wear
- 100-Mesh Inlet Strainer

SUGGESTED SPECIFICATIONS

Wall Mounted Round Bi-Level Drinking Fountain shall be Murdock model GRE24. Drinking Fountain shall be 18 gauge, type 304 stainless steel bowls with a 12 gage, heavy duty stainless steel support arm. Provide 1/4" thick stainless steel mounting plate to securely anchor unit to wall. Access Panels shall be secured with vandal-resistant stainless steel screws. Unit shall be activated by a front mounted, self-closing Pushbutton with Cartridge Valve Assembly, using less than 5 pounds of force to activate with an adjustable stream regulator controlling the water flow. Bubbler shall be polished stainless steel with a Non-Squirt feature and operate on water pressure range of 20-105 PSIG. Provide unit with Elbow Waste connection. **P-Trap shall be installer provided behind wall** (Optional -PT P-Trap with access below fixture is available). Unit shall be certified to Public Law 111-380 (NO-LEAD) and NSF/ANSI/CAN 61. Fixture to meet ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.

Complies
with the
following
standards:



Federal
Public Law
111-380
(No Lead)

NSF/ANSI/CAN 61-2020



Model: GRE27-R Shown

"FOR INDOOR AND OUTDOOR USE"

MODEL:

(Must Specify)

- ☐ GRE24 Satin Stainless Finish
- ☐ GRE25 Green Powder-Coated
- ☐ GRE26 Red Powder-Coated
- ☐ GRE27 Blue Powder-Coated (Shown)

Custom color finishes available upon request

ADA DRINKING FOUNTAIN ORIENTATION

(Must Specify)

- ☐ -L ADA Drinking Fountain Left Side (Opposite)
- ☐ -R ADA Drinking Fountain Right Side (Shown)

OPTIONS

(additional costs may be incurred)

- ☐ -FRA2 Freeze Resistant Valve, Two Valves¹
- ☐ -LOGO Customer specified logo
- ☐ -LSR Bowl with Leaf and Debris Strainer¹
- ☐ -PT 1-1/4" OD P-Trap (Access Below Fixture) (Not Available with -FRA2)
- ☐ -SK8 Cane Detection Skirt (for Non-ADA arm)¹
- ☐ -SOC Concealed Sensor Operation Drinking Fountains - Battery Operated Standard (N/A with -FRA2¹)
- ☐ -316 Type 316 Stainless Steel Construction

Option Notes:

¹See separate option sheet

Product Warranty

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


* Valve specifications:
Minimum/Maximum
Pressure 30 to 100 psi.

GR Series

MODEL GRE24


WALL MOUNTED DRINKING FOUNTAIN

TOP VIEW



NOTES:

1. 1/4" THICK STAINLESS STEEL
STEEL MOUNTING PLATE
2. REMOVABLE ACCESS PANELS
3. DRINKING BUBBLER
4. PUSHBUTTON CARTRIDGE
VALVE ASSEMBLY
5. SHOWN WITH OPTIONAL -PT
1-1/4" OD P-TRAP ASSEMBLY
6. SUPPLY CONNECTION
7. INSTALLER PROVIDED WALL
ANCHORS AND ANCHORING
HARDWARE



GRE24-R SHOWN

GENERAL NOTES:

1. ALL DIMENSIONS ARE IN INCHES
- *2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE AND LOCAL CODES.
3. STOP VALVE NOT PROVIDED.

IMPORTANT: Refer to installation instructions for complete rough-in and technical data.
NOTE: Some options may change standard roughs.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING	Model Number & Options _____ Quantity _____		All dimensions are subject to manufactures tolerance of plus or minus 1/4" nominal and subject to change without notice. Murdock® assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock® Mfg. Member of Morris Group International®. Please visit www.murdockmfg.com for most current specifications.
	Company _____		
	Contact _____	Title _____	
	Signature (Approval for Manufacturing)	Date	

All dimensions are subject to manufactures tolerance of plus or minus 1/4" nominal and subject to change without notice. Murdock® assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock® Mfg., Member of Morris Group International®. Please visit www.murdockmfg.com for most current specifications.