

STAINLESS STEEL

Warning

- ☞ Do not mix different cleaning solutions.
- ☞ Always read cleaning products label for proper use and admonishments.

Normal Cleaning:

Clean weekly or more often as needed (especially high polish or mirror finished surfaces). For best results always rinse well with fresh water and wipe dry with clean soft cloth.

Recommended Cleaning Materials:

- Sponge - natural or artificial
- Nylon or other soft bristle brush
- Micro-fiber Cloth

Recommended Cleaning Solutions:

- Hand dishwashing liquid / soft water solution
- 1:1 Solution, Rubbing Alcohol and Water
- Mild soap / soft water solution
- CRES Clean™ - cleaner / polish
- 3M® Stainless Steel Cleaner - cleaner / polish
- White vinegar / soft water solution (for brightening, removing hard water deposits)
- Club soda

To Remove Stubborn Spots or to Treat a Scratch:

Use a synthetic, abrasive general purpose pad such as Scotch Brite® is recommended. Apply the stainless steel cleaner/polish to the synthetic abrasive pad and CAREFULLY rub out spot with cleaner/polish. **Be sure to rub in the direction of the grain.** Do not allow steel wool to come in contact with the stainless steel. Steel particles can become embedded into the stainless steel surface and create rust.

To Disinfect:

Use a solution of water and rubbing alcohol in a spray bottle or on a micro-fiber cloth and wipe or spray surface, followed by wipe dry with clean dry cloth. Be sure to always wipe or rub in the direction of grain to maintain your finish.

Special Note:

☞ After cleaning for serious problems, let dry and expose to air for at least 24 hours to allow "healing" (restoring of the chromium oxide layer) of stainless steel surfaces.

HIGH POLISH STAINLESS STEEL

Note:

☞ High polish stainless steel surfaces should NEVER come in contact with any abrasive brush, cloth or cleaning agent.

To Remove Smudges and Fingerprints:

Wipe surfaces with a quality Stainless Steel cleaner/polish. Apply using a soft, non-abrasive cloth. Always follow cleaner/polish product instructions and admonishments.

To Remove Dirt and Debris:

Wash surfaces with a mild liquid soap using a soft cloth. Rinse surfaces thoroughly with clean water followed by wiping dry with a soft non-abrasive cloth and stainless steel cleaner/polish.

To Remove Rust Stains:

Wipe surfaces with CRES Clean™ or equivalent cleaner or recommended solutions listed above. Apply using a soft non-abrasive sponge. Rinse surfaces thoroughly with clean water followed by wiping dry with a soft non-abrasive cloth and stainless steel cleaner/polish.

For Tough Problems:

- CRES Clean™ - cleaner / polish
- 3M Stainless Steel Cleaner - cleaner / polish
- #7 chrome polish

Things to Avoid:

- All purpose cleaners containing abrasive particles such as Comet®, Ajax® or Bon Ami®
- Harsh chemicals (strong acidic or alkaline materials such as hydrochloric acid, sodium hydroxide, etc.)
- Any abrasive substance (dirt/mud, ceramic item etc)
- Chlorinated cleansers, sanitizers or bleach of any kind
- Avoid leaving any object made of steel or metal to remain in contact with stainless steel surface (hair pins, paper clips aerosol cans etc.).
- Scotch-Brite® type pads on high polished surfaces
- Seawater or excessively hard water
- Salt or salty foods allowed to dry on surface
- Leaving scratches in metal surface (debris may collect in these preventing surface from "healing")
- Water left to evaporate causes mineral deposits resulting in hard water stains

Note:

☞ For best results, always rinse well with fresh water and wipe dry with a clean soft cloth.

ENVIRO-GLAZE/ POWDER COATING

Warning

- ☞ *Do not mix different cleaning solutions.*
- ☞ *Always read cleaning products label for proper use and admonishments.*

Recommended Cleaning Materials:

- Sponge - natural or artificial
- Nylon or other soft-bristle brush
- Microfiber Cloth

Recommended Cleaning Solutions:

- Hand dishwashing liquid / soft water solution
- Mild soap / soft water solution
- Soft-Scrub[®]
- Comet Soft Cleanser[®]
- Clorox[®]
- Scrubbing Bubbles[®] Gel

Normal Cleaning:

For everyday cleaning use a sponge or cotton cloth soaked in mild soap and wipe-down surface. In industrial or marine locations close attention should be paid to regular care due to harsher atmosphere.

To remove dirt and debris:

Fixture should be periodically washed with a diluted solution of a mild non-abrasive detergent (e.g. Dawn[®]) in cold or ambient temperature water using a soft non-abrasive cloth or chamois.

Fixtures with Enviro-Glaze/ Powder Coating

Never use a plumber's snake on an Enviro-Glazed Toilet or Urinal to clear severe clogs. The use of the tool will damage the finish, scratch the paint and cause corrosion voiding the warranty. Fixture must be dismantled from the structure sewer connection (floor/wall) and the snake used from the connection into the sewer. Any clog in the fixture trap can be accessed from the outlet of the trap after dismantling.



Solutions to Avoid:

- Kaboom[®]
- Lysol[®] Gel
- Lysol[®] Cling
- The Works
- Petrol products
- Acetates
- Abrasive powders
- Scouring pads
- Toilet cleaners
- Ceramic tile cleaners
- Cleaners containing more than 1% ammonia
- Cleaners containing acids or lye
- Cleaners containing enzymes



Things to Avoid:

- Excessively hot solutions
- Cleaning with a metal brush can scratch or mar the finish which can cause corrosion voiding the warranty
- Using any solvent based solution or abrasive type cleaners
- Applying excessive force during the cleaning process